



Supreme Synth 5W30

Description

A universal, synthetic fuel economy motor oil developed according to the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Performance Level

Performance level
ACEA C3
API SN
BMW Longlife-04
GM dexos 2
MB 229.51/229.52
VW 505.00/505.01

Typicals

Density at 15 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	6040
Viscosity 40 °C, mm²/s	70,30
Viscosity 100 °C, mm²/s	11,90
Viscosity Index	166
Flash Point COC, °C	246
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,78

