



Supreme HyperSynthetic 5W40

Description	<p>A very modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> - a high and very stable viscosity index - a high resistance against shearing - a fast cold start - a very strong resistance against oxidation - a safe lubrication film at very high temperatures - a very good detergency and dispersion - a very strong protection against wear, corrosion and foaming 	
Application	<p>A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans for which the most modern specifications are required.</p>	
Performance Level	<p>Performance level ACEA A3/B4 API SN/CF BMW Longlife-01 Fiat 9.55535-M2 GM LL-B-025 MB 229.3/226.5 Porsche A40 Renault RN0700/RN0710 VW 502.00/505.00</p>	
Typicals	<p>Density at 15 °C, kg/l Viscosity -30 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %</p>	<p>0,851 5740 90,20 15,00 173 223 -42 10,3 1,33</p>

